

LGMG

S1212 II

HYDRAULIC MOTOR DRIVE
SCISSOR LIFT

- Large lower control panel
- Entire range designed for indoor and outdoor use
- Universal key components
- More convenient to maintain
- Optional lithium battery for the entire product range



LGMG HYDRAULIC MOTOR DRIVE SCISSOR LIFT

SPECIFICATIONS

| MODELS | S1212 II (S4046 II) | |
|---|------------------------------------|---|
| Measurements | Metric | Imperial |
| Work Height Max. | 14/9.5m <small>(in/out)</small> | 45'11"/31'2" <small>(in/out)</small> |
| A Platform Height-Raised | 12/7.5m <small>(in/out)</small> | 39'4"/24'7" <small>(in/out)</small> |
| B Platform Length | 2.26m | 7'5" |
| C Platform Width | 1.12m | 3'8" |
| D Overall Length | 2.49m | 8'2" |
| E Overall Width | 1.18m | 3'10" |
| F Overall Height-Guardrails Up | 2.63m | 8'8" |
| G Overall Height-Guardrails Down | 1.84m | 6' |
| H Extension Deck | 0.9m | 2'11" |
| I Wheelbase | 1.85m | 6'1" |
| Ground Clearance(Stowed/Raised) | 100/20mm | 4"/1" |

PRODUCTIVITY

| | | |
|----------------------------------|-------------------|---------|
| Max. Platform Occupants | 2 (in) / 1(out) | |
| Platform Capacity | 320kg | 705 lbs |
| Platform Capacity-Extension Deck | 120kg | 265 lbs |
| Drive Height | Full Height | |
| Gradeability-Stowed | 25% | |
| Min. Turning Radius | 2.45m | 8' |
| Raise/Lower Speed | 65s / 60s | |
| Brakes | Rear-wheel Brake | |
| Drive Mode | 4x2 | |
| Tire Type | Solid Non-marking | |
| Tire Size | 380x130mm | 15"x5" |

POWER

| | | |
|----------------------------|-----------|--|
| Power Source | 24V 300Ah | |
| Power Source (S1212 II-Li) | 24V 230Ah | |

HYDRAULIC SYSTEM

| | | |
|------------------------|-----|--------|
| Hydraulic Oil Capacity | 23L | 6.1gal |
|------------------------|-----|--------|

WEIGHT


| | | |
|-------------------------|--------|----------|
| Machine Weight(CE/ANSI) | 2970kg | 6548 lbs |
|-------------------------|--------|----------|

STANDARD FEATURES

| | |
|----------------------|------------------------------------|
| Proportional control | Indoor and outdoor rated |
| Foldable guardrail | Emergency stop device |
| Manual brake release | Swing-out component tray |
| Emergency descent | Tilt alarm with lift cut-out |
| Pothole guard | Overload sensing system |
| Self-lock entry gate | Descent alarm with flashing beacon |
| All motions alarm | Intelligent diagnostic system |
| Full-height drive | Solid non-marking tires |

OPTIONAL

| | |
|----------------------|-----------------------------|
| AC power to platform | Anti-collision protection |
| Voice alarm system | Maintenance-free battery |
| Telematics | Biodegradable hydraulic oil |



Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

This brochure comes into effect in May, 2023.

LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China
Email: sales@lmgm.com.cn Tel: +86 531 6787 9283

LGMG Europe B.V.

Address: Donker Duyvisweg 301, 3316 BL Dordrecht, The Netherlands
Email: sales@lmggeurope.com Tel: +31 850 642 777

LGMG North America Inc.

Address: 4105 Live Oak Drive, Suite 100, The Colony, Texas 75056 United States
Email: sales@lmgmna.com Tel: +1 833 288 5464

www.lmgglifts.com



LGMG

RELIABILITY IN ACTION